

BATTERY

GP-5123140-LVT



Lithium-LiFePO4 battery
51.2V,314Ah

Features

This series is a complete solution for the lithium iron phosphate battery system for the home energy storage field. There are three types of wall-mounted, vertical structures and rack. The system is safe and reliable. It can be used in home storage, industrial and commercial energy storage and other fields.



Product Features



Safe, reliable and long life



Dynamic identification, automatic paralleling, no need for DIP switches



Support Bluetooth, mobile APP switching PCS protocol



Flexible expansion, the number of parallel machines supports up to 15



CAN/RS485/
LAN interface



Visualization, LCD screen display



Supports mixed parallel of old and new batteries



Efficient operation and maintenance


Compatible With Inverter Brands

MACQUARIE	SOROTEC	GROWATT	DEYE	VITVON	SERMATEC	LUXPOWER	GSSTES
SMA	GOODWE	SREN	HuiNeng	iYPower	OUKITEL	ROBOROCK	Sunsunk
Voltronic	Pylontech	MustPower	SAKO	Senergy	Felicity	KSTAR	Solis


GREAT POWER FROM GOGO POWER

BATTERY


GP-5123140-LVT



System Specifications



Panel silkscreen preview



Battery communication interface preview

Model	GP-5123140-LVT
Voltage(V)	43.2~58.4V
Cell	3.2V314Ah
Number of parallel machines	15PCS
Nominal voltage(V)	51.2
Nominal Capacity(Ah)	314
Nominal Energy(kWh)	16.07
Maximum power output(kWh)	7.6
Maximum discharge current(A)	150
Maximum charging current(A)	120
Recommended discharge voltage(Min)(V)	48(40)
Recommended charging voltage (Max) (V)	56(58.4)
Cycles(25°C,0.5C,DOD80%)	≥8000
Charging temperature(°C)	0~55
Discharge temperature(°C)	-20~55
Operating humidity	<95%R.H
Communication mode	CAN/RS485
Dry contact	Customized by demand
Optional modules	Bluetooth
Product size(W*D*H,mm)	830*475*257.5
Packing size(W*D*H,mm)	910*555*440
Protection class	IP21
System weight(kg)	Approx 137.9